


AZVAFCB2MD4 - Control board with Midea / Kaysun V5 Protocol (HAHB) communication

Location:	Approval:
Engineer:	Date:
Submitted to:	Construction:
Submitted by:	Unit #:
Reference:	Drawing #:
Additional Info:	

MODEL DESCRIPTION

Configurable electronic board with a communication gateway, that controls the system through wired and wireless devices. Externally powered at 110/230 Vac. Wall mounted. Functionalities:

- Controls the status of the thermostats (up to 10 zones).
- Controls the proportionality and the minimum air supply of the dampers.
- Control of optional auxiliary heat (up to two stages).
- Management of the control gateway.
- Communication with units of integral control of the installation.
- Communications with other external control systems through integration bus.



[Click to download](#)

TECHNICAL SPECS

Power supply and consumption	
Type of power supply	Vac
V max	110 / 230 Vac
I max	250 mA
Frequency	60 / 50 Hz
Stand-by consumption	400 mW
Module over-current protection	250 mA

Airzone connection bus	
N° of ports	3
Shielded twisted pair	AWG 23 - 2 wired + AWG 20 - 2 wired (2 x 0.22 + 2 x 0.5 mm ²)
V max	12 V

AC unit bus	
N° of ports	1
Shielded twisted pair	AWG 20 - 4 wired (2 x 0.22 + 2 x 0.5 mm ²)
V max	12 V

Automation bus	
N° of ports	1
Shielded twisted pair	AWG 20 - 4 wired (2 x 0.22 + 2 x 0.5 mm ²)
Communications protocol	MODBUS RS-485 Par - 19200 bps

Relay outputs	
N° of relays	2
V max	48 V
I max	1 A

Digital inputs	
N° of inputs	1
State	Voltage-free

Protection by probe	
Type of probe	NTC
Reading accuracy	1 °F (0.1°C)


Operating temp.	
Storage	- 4 ... 158 °F (- 20 ... 70 °C)
Operation	32 ... 113 °F (0 ... 45 °C)

Mechanical aspects	
Protection class	IP 20
Weight	1.36 lb (616 g)
Maximum Operating Height	6561.7 ft (2000 m)

DIMENSIONAL DRAWINGS



INSTALLATION



The only compatible manufacturer's wired control is KJR-120X or equivalent.

SPARE PARTS

- AZPV8WIRE10 - Connection to Indoor unit 8.2 ft (2.5 m) / AWG 24 - 6 wired (6x0.2 mm²)
- AZX8GTCMD4 - Airzone - Midea V5 protocol (HAHB) controller gateway

ACCESORIES

- AZPV8WIREU - Universal 6-pin 8.2 ft (2.5 m) extension cable for Airzone gateway / Aidoo



Marie Curie, 21
29590 Málaga, Spain

