

AIDOO Pro

One Device, Multiple Integration Options
for Inverter/VRF



Explore the
Airzone Cloud
App Demo



DUAL WIFI

{ REST:API }



BACnet

Modbus
RTU Port

BACnet, Home and Building Automation,
Voice Control, Smart Thermostat Control
& More



Climate
Control



Cloud
Control



2-way
communication



Voice Control &
Home and Building
Management
Systems



12 VdC
relay output for
auxiliary heat



Easy
configuration



Compatible
with smart
thermostats

Smart Control

- **Compatible with both ducted and ductless HVAC systems** in residential and commercial applications.
- **Integration with any Home Automation/BMS system** via local and Cloud API.
- **Communication port** for BACnet/Modbus integration (BACnet MS/TP and IP).
- **12V DC relay output** for auxiliary heat, which allows for lockout temperature (rebates available).
- **Digital input** for open window contact or occupancy sensors.
- **24/7 Smart diagnostics** with reading of indoor unit warnings and errors.
- **Smart thermostat integration** (such as Nest, Honeywell and Ecobee) via Cloud – keeping Inverter/VRF features intact.
- **Self-powered** by external power supply provided in the box.
- **Dual Wi-Fi capable:** 2.4/5GHz Wi-Fi connection.



1. Power supply
2. 24V thermostat connection
3. Aux heat output
4. Digital input
5. Modbus/BACnet port
6. Unit connection port



- All zones on/off.
- Temperature setpoint.
- Operating mode.



24/7 remote diagnostics with Airtools

Remote error code readings & firmware updates.



Lockout Temperature

This customizable function prevents the heat pump from operating in inefficient outdoor conditions, such as extremely cold temperatures. The lockout can also be applied to auxiliary heat sources, disabling them at the set temperature once outdoor conditions are favorable for the heat pump.

Your All-in-One HVAC Integration Hub



866 521 0263 | airzonecontrol.com

AIDOO IS
A PRODUCT
MADE BY

