

Round diffuser with motorized insulated plenum DFCI_PAM



Description

Round diffuser DFCI to supply air in 4 directions that enables the air supply. Easy to disassemble to facilitate its maintenance.

Measures		QV (m3/h)													
A'k (dm^2)	D (mm)	150		200		300		400		500		600		800	
1,4	150	22,0	1,7	31,0	2,2	45,0	3,3								
		3,0	12,2	4,0	21,7	6,0	48,7								
1,9	200	9,0	1,3	19,0	1,7	33,0	2,6	42,0	3,5						
		2,2	4,9	2,9	8,7	4,4	19,7	5,8	34,9						
2,6	250			6,0	1,3	20,0	2,0	29,0	2,7	37,0	3,3	43,0	4,0		
				2,1	3,4	3,2	7,7	4,3	13,8	5,3	21,5	6,4	31,0		
3,4	300					9,0	1,6	19,0	2,1	26,0	2,7	32,0	3,2	42,0	4,2
						2,5	3,5	3,3	6,2	4,1	9,7	4,9	13,9	6,5	24,8
4,3	350							9,0	1,7	17,0	2,2	23,0	2,6	32,0	3,5
								2,6	3,1	3,2	4,8	3,9	6,9	5,2	12,3

The user is responsible for the correct interpretation of the data obtained.

AIRZONE reserves the right to modify the technical characteristics and dimensions of the products of this tool without prior notice.

For any doubt or clarification contact projects@airzonecontrol.com

NR	Lt	Noise level in dBA	Range in meters
V	Pa	Flow speed in m/s	Pressure in Pascals

AK: Effective area (dm2)	L: Length (mm)
QV: Flow (m3/h)	H: Height (mm)