

Motorized grille of linear slats fixed at 15° deflex RLQV+CPRR



Description

Extruded aluminum supply grilles to enable the air flow supply. 26-mm standard frame.

Measures			QV (m3/h)																	
L (mm)	H (mm)	A'k (dm^2)	100		200		300		400		600		800		1000		1500		2000	
300	100	1,0	24,0	7,6	36,0	15,2	44,0	22,8												
			2,8	4,7	5,6	19,0	8,3	42,7												
200	150	1,0	24,0	7,6	36,0	15,2	44,0	22,8												
			2,8	4,7	5,6	19,0	8,3	42,7												
400	100	1,3			32,0	11,0	39,0	16,6	45,0	22,1										
					4,3	11,3	6,5	25,3	8,6	45,0										
300	150	1,6			29,0	8,6	36,0	12,9	42,0	17,3										
					3,5	7,5	5,3	16,9	7,1	30,1										
200	200	1,3			32,0	11,0	39,0	16,6	45,0	22,1										
					4,3	11,3	6,5	25,3	8,6	45,0										
500	100	1,7			27,0	7,8	35,0	11,6	40,0	15,5	48,0	23,3								
					3,2	6,3	4,9	14,2	6,5	25,3	9,7	56,9								
600	100	2,0					32,0	9,6	38,0	12,7	46,0	19,1	51,0	25,5						
							4,2	10,3	5,6	18,3	8,3	41,3	11,1	73,4						
400	150	2,1					31,0	8,8	37,0	11,7	45,0	17,6	50,0	23,4						
							3,9	9,0	5,2	16,0	7,8	35,9	10,4	63,9						
300	200	2,1					31,0	8,8	37,0	11,7	45,0	17,6	50,0	23,4						
							3,9	9,0	5,2	16,0	7,8	35,9	10,4	63,9						
500	150	2,6							34,0	9,3	42,0	14,0	47,0	18,6						
									4,3	11,0	6,5	24,7	8,6	43,9						
300	250	2,6							34,0	9,3	42,0	14,0	47,0	18,6						
									4,3	11,0	6,5	24,7	8,6	43,9						
600	150	3,1							31,0	7,2	39,0	10,9	45,0	14,5	49,0	18,1				
									3,5	7,3	5,3	16,4	7,1	29,1	8,8	45,5				
500	200	3,6							29,0	6,2	37,0	9,3	43,0	12,3	47,0	15,4				
									3,1	5,6	4,7	12,6	6,2	22,4	7,8	35,0				
300	300	3,1							31,0	7,2	39,0	10,9	45,0	14,5	49,0	18,1				
									3,5	7,3	5,3	16,4	7,1	29,1	8,8	45,5				
600	200	4,3									34,0	7,4	40,0	9,8	45,0	12,3				
											3,9	8,6	5,2	15,4	6,5	24,0				
400	300	4,3									34,0	7,4	40,0	9,8	45,0	12,3				
											3,9	8,6	5,2	15,4	6,5	24,0				
500	300	5,4									31,0	5,5	37,0	7,3	41,0	9,1	50,0	13,7		
											3,1	5,3	4,1	9,5	5,1	14,8	7,7	33,4		
600	300	6,6													39,0	7,2	47,0	10,8	53,0	14,4
																4,2	10,0	6,3	22,6	8,5

The user is responsible for the correct interpretation of the data obtained.

AIRZONE reserves the right to modify the technical characteristics and dimensions of the products of this tool without prior notice.

For any doubt or clarification contact projects@airzonecontrol.com

NR	Lt	Noise level in dBA	Range in meters
V	Pa	Flow speed in m/s	Pressure in Pascals

AK: Effective area (dm2)	L: Length (mm)
QV: Flow (m3/h)	H: Height (mm)